

In re Patent Application of
Gerald A. Pierson
Serial No. **09/938,288**
Filed **August 23, 2001**

In the Claims:

Please substitute the currently amended Claims as set forth below in a complete listing of the pending claims. Struckthrough language indicates a deletion, and underlined language indicates an addition. The amendments include no new matter and are fully supported in the application as filed.

35.(currently amended) A method of forming an optical compact disc, the method comprising the step of molding at least one plastic layer having a pattern of digital data encoded thereon, the wherein said at least one plastic layer having has a major elevational portion and a minor elevational portion, the major elevational portion having the encoded digital data thereon and the minor elevational portion being devoid of the encoded digital data.

36.(original) A method as defined in Claim 35, wherein the major elevational portion is formed in a medial portion of the optical compact disc and has first and second pairs of spaced-apart outer side peripheries defining outer boundaries of the major elevational portion, each of the first pair of spaced-apart outer side peripheries arcuately extending between each of the second pair of spaced-apart outer side peripheries, and each of the second pair of spaced-apart outer side peripheries extending substantially linearly between each of the first pair of spaced-apart outer peripheries.

37.(original) A method as defined in Claim 36, wherein the encoded digital data of the major portions of the plastic layer is formed within a circular data zone and comprises less than the entire surface area of the major elevational portion of the plastic layer.

In re Patent Application of
Gerald A. Pierson
Serial No. 09/938,288
Filed August 23, 2001

38.(original) A method as defined in Claim 37, wherein the step of molding the plastic layer includes molding an opening extending through a medial portion of the plastic layer.

39.(original) A method as defined in Claim 38, further comprising the step of applying a metallic layer on at least portions of the plastic layer.

40.(original) A method as defined in Claim 39, further comprising the step of applying a third protective layer on at least the metallic layer for protecting the metallic layer.

41.(original) A method as defined in Claim 40, further comprising the step of applying an indicia bearing layer on the third layer and having a generally planar upper surface for displaying indicia therefrom.

42.(currently amended) A method of forming an optical compact disc, the method comprising the step of:

molding a compact disc having a pattern of digital data encoded ~~thereon, the compact disc having on a surface bounded by~~ first and second pairs of spaced-apart outer side peripheries defining outer boundaries of at least portions of the disc, each of the first pair of spaced-apart outer side peripheries arcuately extending between each of the second pair of spaced-apart outer side peripheries extending substantially linearly between each of the first pair of spaced-apart outer peripheries.

In re Patent Application of
Gerald A. Pierson
Serial No. 09/938,288
Filed August 23, 2001

43.(original) A method as defined in Claim 42, further comprising positioning an opening in a medial portion of the compact disc, wherein each of the arcuately-extending first pair of spaced-apart outer side peripheries of the portion of the disc are centered about an axis extending through the medial opening and substantially perpendicular to the linearly-extending second pair of spaced-apart outer side peripheries, and wherein a radius extending from a medial portion of the medial opening to each of the arcuately-extending first pair of spaced-apart outer side peripheries of the major elevational portion is less than 1.6 inches.